



Conexión Interlock Hembra Métrica 45° (Serie S)



CODIGO	DESCRIPCION	D.N.	HOSE SIZE	T MM	T PITCH mm	A MM	A INCH	D MM	D INCH	H MM	H INCH	BAR	PSI	BAR	PSI
LAMMDKO420S16	CONEXIÓN INTERLOCK HM 10-20S 45(KF45E1030S20)	-10	5/8 "	M 30.0	X 2.00					20.00	0.790 "			420 bar	6091
LAMMDKO420S19	CONEXIÓN INTERLOCK HM 12-20S 45(KF45E1230S20)	-12	3/4 "	M 30.0	X 2.00	61.50	2.420 "	27.00	1.060 "	20.00	0.790 "	36	1.420 "	420 bar	6091
LAMMDKO425S19	CONEXIÓN INTERLOCK HM 12-25S 45(KF45E1236S25)	-12	3/4 "	M 36.0	X 2.00	67.50	2.660 "	28.00	1.100 "	25.00	0.980 "	46	1.810 "	420 bar	6091
LAMMDKO425S25	CONEXIÓN INTERLOCK HM 16-25S 45(KF45E1636S25)	-16	1 "	M 36.0	X 2.00	86.00	3.390 "	38.00	1.500 "	25.00	0.980 "	46	1.810 "	414 bar	6004
LAMMDKO430S25	CONEXIÓN INTERLOCK HM 16-30S 45(KF45E1642S30)	-16	1 "	M 42.0	X 2.00	86.50	3.410 "	38.00	1.500 "	30.00	1.180 "	50	1.970 "	280 bar	4061
LAMMDKO430S32	CONEXIÓN INTERLOCK HM 20-30S 45(KF45E2042S30)	-20	1 1/4 "	M 42.0	X 2.00	103.00	4.060 "	35.00	1.380 "	30.00	1.180 "	50	1.970 "	250 bar	3626
LAMMDKO438S32	CONEXIÓN INTERLOCK HM 20-38S 45(KF45E2052S38)	-20	1 1/4 "	M 52.0	X 2.00	103.00	4.060 "	35.00	1.380 "	38.00	1.500 "	60	2.360 "	250 bar	3626
LAMMDKO438S38	CONEXIÓN INTERLOCK HM 24-38S 45(KF45E2452S38)	-24	1 1/2 "	M 52.0	X 2.00	117.50	4.630 "	45.00	1.770 "	38.00	1.500 "	60	2.360 "	250 bar	3626

La información recogida en esta ficha (Catálogo) es de carácter orientativo y puede ser modificada o no sin previo aviso. UTECSA no se hace responsable de una correcta utilización del producto, salvo las referentes a defectos de fabricación.