



## Conexión Interlock Hembra Métrica 90° (Serie S)



CODIGO	DESCRIPCION	D.N.	HOSE SIZE	T MM	T PITCH mm	A MM	A INCH	D MM	D INCH	H MM	H INCH	BAR	PSI	BAR	PSI
LAMMDKO920S16	CONEXIÓN INTERLOCK HM 10-20S 90(KF90E1030S20)	-10	5/8 "	M 30.0	X 2.00					20.00	0.790 "			420 bar	6091
LAMMDKO920S19	CONEXIÓN INTERLOCK HM 12-20S 90(KF90E1230S20)	-12	3/4 "	M 30.0	X 2.00	54.00	2.130 "	59.00	2.320 "	20.00	0.790 "	36	1.420 "	420 bar	6091
LAMMDKO925S19	CONEXIÓN INTERLOCK HM 12-25S 90(KF90E1236S25)	-12	3/4 "	M 36.0	X 2.00	54.00	2.130 "	59.00	2.320 "	25.00	0.980 "	46	1.810 "	420 bar	6091
LAMMDKO925S25	CONEXIÓN INTERLOCK HM 16-25S 90(KF90E1636S25)	-16	1 "	M 36.0	X 2.00	70.50	2.780 "	75.00	2.950 "	25.00	0.980 "	46	1.810 "	414 bar	6004
LAMMDKO930S25	CONEXIÓN INTERLOCK HM 16-30S 90(KF90E1642S30)	-16	1 "	M 42.0	X 2.00	70.50	2.780 "	75.00	2.950 "	30.00	1.180 "	50	1.970 "	280 bar	4061
LAMMDKO930S32	CONEXIÓN INTERLOCK HM 20-30S 90(KF90E2042S30)	-20	1 1/4 "	M 42.0	X 2.00	90.50	3.560 "	86.00	3.390 "	30.00	1.180 "	50	1.970 "	250 bar	3626
LAMMDKO938S32	CONEXIÓN INTERLOCK HM 20-38S 90(KF90E2052S38)	-20	1 1/4 "	M 52.0	X 2.00	90.50	3.560 "	86.00	3.390 "	38.00	1.500 "	60	2.360 "	250 bar	3626
LAMMDKO938S38	CONEXIÓN INTERLOCK HM 24-38S 90(KF90E2452S38)	-24	1 1/2 "	M 52.0	X 2.00	97.50	3.840 "	94.00	3.700 "	38.00	1.500 "	60	2.360 "	250 bar	3626

La información recogida en esta ficha (Catálogo) es de carácter orientativo y puede ser modificada o no sin previo aviso. UTECSA no se hace responsable de una correcta utilización del producto, salvo las referentes a defectos de fabricación.